

# Industrial Grinders HERITAGE SERIES

**Cleco®**





**NEW**  
**Cleco®**  
**HERITAGE SERIES**

**Durable.**  
**Powerful.**  
**Lightweight.**

Cleco® industrial grinders have been trusted in the industry for decades.

The design has been imitated by numerous competitors but its ruggedness and durability have never been duplicated.

Introducing the new Cleco® Heritage 216, 236, and 25 Series, with the latest in advanced material and motor technology.

These tools deliver durability, power, yet are lighter and more capable than before.





## Heritage 216 Series



This compact and powerful grinder family has been copied by many competitors since its debut 30 years ago. Today, Cleco® brings you a grinder that is up to 40% lighter and more efficient than ever.

- Compact and powerful 0.7HP motor (0.5 Kw)
- Lightweight and rugged advanced alloy housing
- 12 variations available to meet any range of performance needs
- Accommodates up to 1" ( 25mm) Carbide Burrs, 4" (100mm) Type 1 Wheels, and 4 1/2" (115mm) Type 27 Wheels
- Recognizable in its high visibility Cleco® Orange

## Heritage 236 Series



Versatility and ruggedness defines the 236 Series by serving demanding fields such as foundries, shipyards, and other heavy industries world-wide.

- Robust and efficient 0.9HP motor (0.7 Kw)
- Lightweight and rugged advanced alloy housing; including an ultra-compact angle head
- 35 variations available to meet any range of performance needs
- Accommodates up to 1" ( 25mm) Carbide Burrs, 4" (100mm) Type 1 Wheels, 5" (125mm) Type 27 Wheels, and 1.25" (31mm) Cone or Plug Wheel
- Recognizable in its high visibility Cleco® Orange

## Heritage 25 Series



As **THE** heavy-duty workhorse of the family, the 25 Series is engineered for serious material removal. Lightweight, rugged, and powerful; these tools mean business.

- Powerful and governed 1.4HP motor (1.0 Kw) for maximum material removal
- Lightweight and rugged advanced alloy housing
- 16 models, including the lightest-weight extended inline grinders weighing only 3.0 lbs (1.4 Kg)
- Accommodates up to 1" ( 25mm) Carbide Burrs, 2" (50mm) Mounted Wheels, 7" (180mm) Type 27 Wheels, to 1.25" (31mm) Cone or Plug Wheels
- Recognizable in its high visibility Cleco® Orange

MODEL	DESCRIPTION	TERMINATION (1)	ABRASIVE CAPACITY (2)	MAX. FREE SPEED		POWER (3)		LENGTH		WEIGHT		SCFM @ F/S
				rpm	hp	Kw	in	mm	lbs	kg		
<b>HERITAGE 216 SERIES   0.7HP (0.5Kw)</b>												
216GLF-115A-C4	Right Angle Grinder, Front Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	11,500	0.6	0.4	7.1	180	2.4	1.1	25	
216GLFC-165A-C4	Right Angle Grinder, Front Exhaust	1/4" Collet	3/4" (19mm) Carbide Burr	16,500	0.6	0.4	9.1	231	1.7	0.8	25	
216GLSC-165A-C4	Right Angle Grinder, Side Exhaust	1/4" Collet	3/4" (19mm) Carbide Burr	16,500	0.6	0.4	6.3	160	1.7	0.8	25	
216GLF-115A-W3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	11,500	0.6	0.4	7.1	180	2.7	1.2	25	
216GLFB-135A-W3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	13,500	0.6	0.4	9.6	244	2.1	1.0	25	
216GLSB-135A-W3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	13,500	0.6	0.4	9.1	231	2.4	1.1	25	
216GLF-115A-D3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	11,500	0.6	0.4	7.1	180	2.7	1.2	25	
216GLF-115A-D3T45	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4 1/2" (115mm) Type 27	11,500	0.6	0.4	7.1	180	2.7	1.2	25	
216GLRB-135A-D3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	13,500	0.6	0.4	9.1	231	2.7	1.2	25	
216GLSB-135A-D3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	13,500	0.6	0.4	9.1	231	2.4	1.1	25	
216GLFB-250-C4	Inline Grinder, Front Exhaust	1/4" Collet	3/4" (19mm) Carbide Burr	25,000	0.7	0.5	6.3	160	1.3	0.6	27	
216GLSB-250-C4	Inline Grinder, Side Exhaust	1/4" Collet	3/4" (19mm) Carbide Burr	25,000	0.7	0.5	6.3	160	1.3	0.6	27	

<b>HERITAGE 236 SERIES   0.9HP (0.7Kw)</b>												
236GLF-115A-C4	Right Angle Grinder, Front Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	11,500	0.8	0.6	7.6	193	2.6	1.2	29	
236GLR-115A-C4	Right Angle Grinder, Rear Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	11,500	0.8	0.6	8.3	211	2.1	1.0	36	
236GLSC-115A-C4	Right Angle Grinder, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	11,500	0.8	0.6	9.6	244	2.0	0.9	28	
236GLFC-165A-C4	Right Angle Grinder, Front Exhaust	1/4" Collet	4" (100mm) Type 1	16,500	0.8	0.6	9.6	244	2.0	0.9	30	
236GLR-115A-D3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	11,500	0.8	0.6	8.3	211	2.5	1.1	36	
236GLRB-135A-D3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	13,500	0.6	0.4	7.6	193	2.0	0.9	33	
236GLF-115A-W3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	11,500	0.8	0.6	7.6	193	3.0	1.4	29	
236GLFB-135A-W3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	13,500	0.8	0.6	9.6	244	2.0	0.9	29	
236GLS-115A-W3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	11,500	0.8	0.6	8.3	211	2.5	1.1	33	
236GLSB-115A-W3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	11,500	0.6	0.4	9.6	244	2.0	0.9	28	
236GLR-115A-D3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	13,500	0.6	0.4	9.6	244	2.0	0.9	28	
236GLF-115A-D3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	11,500	0.8	0.6	7.6	193	3.0	1.4	29	
236GLFB-135A-D3T4	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	13,500	0.8	0.6	9.6	244	2.0	0.9	29	
236GLR-115A-D3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	8.3	211	2.5	1.1	36	
236GLRB-135A-W3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	13,500	0.6	0.4	7.6	193	2.0	0.9	36	
236GLS-115A-D3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	11,500	0.8	0.6	7.6	193	2.5	1.1	33	
236GLSB-135A-D3T4	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 27	13,500	0.6	0.4	9.6	244	2.0	0.9	28	
236GLF-115A-D3T45	Right Angle Grinder, Front Exhaust	3/8"-24 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	7.6	193	3.0	1.4	29	
236GLR-115A-D3T5	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	5" (125mm) Type 27	11,500	0.8	0.6	8.3	211	2.5	1.1	36	
236GLR-115A-W3T4	Right Angle Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	11,500	0.8	0.6	8.3	211	2.5	1.1	36	
236GLRE-115A-D5T45	Right Angle Grinder, Rear Exhaust	5/8"-11 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	7.6	193	3.5	1.6	32	
236GLS-115A-D3T45	Right Angle Grinder, Side Exhaust	3/8"-24 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	7.6	193	2.5	1.1	33	
236GLS-115A-D5T45	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	7.6	193	2.5	1.1	33	
236GLR-115A-D5T45	Right Angle Grinder, Rear Exhaust	5/8"-11 External Thread	4 1/2" (115mm) Type 27	11,500	0.8	0.6	8.3	211	2.5	1.1	36	
236GEL-240-C4	Inline Grinder, Extended, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	24,000	0.9	0.7	12.4	312	2.3	1.0	30	
236GELR-180-C4	Inline Grinder, Extended, Rear Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	18,000	0.6	0.4	12.3	312	2.2	1.0	27	
236GLF-180-C4	Inline Grinder, Front Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	18,000	0.9	0.7	6.8	173	1.4	0.6	30	
236GLF-250-C4	Inline Grinder, Front Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	25,000	0.9	0.7	6.8	173	1.4	0.6	30	
236GLR-250-C4	Inline Grinder, Rear Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	25,000	0.9	0.7	7.4	188	1.3	0.6	35	
236GLS-180-C4	Inline Grinder, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	18,000	0.9	0.7	6.8	173	1.4	0.6	28	
236GLS-240-C4	Inline Grinder, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	24,000	0.9	0.7	6.8	173	1.4	0.6	29	
236GLR-180-C4	Inline Grinder, Rear Exhaust	1/4" Collet	4" (100mm) Type 27	18,000	0.9	0.7	7.4	188	1.3	0.6	35	
236GLR-200-C4	Inline Grinder, Rear Exhaust	1/4" Collet	4" (100mm) Type 27	20,000	0.9	0.7	7.4	188	1.3	0.6	35	
236GLF-250-C6	Inline Grinder, Front Exhaust	3/8" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	25,000	0.9	0.7	6.8	173	1.4	0.6	30	
236GLR-180-W3T4	Inline Grinder, Rear Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	18,000	0.9	0.7	7.3	185	1.8	0.8	35	
236GELR-180-P3T	Inline Grinder, Extended, Rear Exhaust	3/8"-24 External Thread	1.25" (31mm) Cone or Plug Wheel	18,000	0.6	0.4	12.3	312	2.3	1.0	27	
236GEL-240-P3T	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	1.25" (31mm) Cone or Plug Wheel	24,000	0.9	0.7	12.3	312	2.3	1.0	30	

<b>HERITAGE 25 SERIES   1.4HP (1.0Kw)</b>												
25GL-60A-D5T7	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	7" (180mm) Type 27	6,000	1.2	0.9	10.0	254	5.6	2.5	12	
25GL-60A-W5T7	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	7" (180mm) Type 1	6,000	1.2	0.9	10.0	254	5.6	2.5	12	
25GL-77A-D5T7	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	7" (180mm) Type 27	7,700	1.2	0.9	10.0	254	5.6	2.5	12	
25GL-85A-D5T7	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	7" (180mm) Type 27	8,500	1.2	0.9	10.0	254	5.6	2.5	12	
25GL-85A-W5T7	Right Angle Grinder, Side Exhaust	5/8"-11 External Thread	7" (180mm) Type 1	8,500	1.2	0.9	10.0	254	5.6	2.5	12	
25GELC-120-C4	Inline Grinder, Extended, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	12,000	1.4	1.0	14.4	368	3.0	1.4	12	
25GELC-180-C4	Inline Grinder, Extended, Side Exhaust	1/4" Collet	1" (25mm) Car. Burr, 2" (50mm) Wheel	18,000	1.4	1.0	14.5	368	3.0	1.4	30	
25GELC-140-P3T	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	1.25" (31mm) Cone or Plug Wheel	14,000	1.4	1.0	14.5	368	3.0	1.4	21	
25GELC-180-P3T	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	1.25" (31mm) Cone or Plug Wheel	18,000	1.4	1.0	14.5	368	3.0	1.4	30	
25GELC-120-W3T25	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	2.5" (63mm) Type 1	12,000	1.4	1.0	14.4	368	3.4	1.5	12	
25GELC-120-W3T3	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	3" (75mm) Type 1	12,000	1.4	1.0	14.4	368	3.7	1.7	12	
25GELC-140-W3T3	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	3" (75mm) Type 1	14,000	1.4	1.0	14.5	368	3.7	1.7	21	
25GELC-180-W3T3	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	3" (75mm) Type 1	18,000	1.4	1.0	14.9	378	3.7	1.7	30	
25GELC-120-W3T4	Inline Grinder, Extended, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	12,000	1.4	1.0	14.4	368	3.7	1.7	12	
25GL-120-W3T4	Inline Grinder, Side Exhaust	3/8"-24 External Thread	4" (100mm) Type 1	12,000	1.4	1.0	10.0	254	3.0	1.4	12	
25GELC-180-P5T	Inline Grinder, Extended, Side Exhaust	5/8"-11 External Thread	1.25" (31mm) Cone or Plug Wheel	18,000	1.4	1.0	14.9	378	3.2	1.5	30	

Air Inlet: 216G and 236G series = 1/4" NPT, 25G series = 3/8" NPT

(1) 1/4" Collet will accommodate a shank size of 7/32" (5.56mm) to 1/4" (6.35mm). Additional Collet sizes available as an accessory.

(2) Note: Mounted Wheel capacity depends on wheel diameter, thickness and overhang. Consult cutting device manufacturer for speed recommendations.

(3) Note: All tools performance rated at 90psi (6.2 bar)

